



F900

E934F Single Pan Electric Fryer with Filtration

Key features

- Oil capacity is just 20 litres
 - Efficient to heat and economical to fill up
- Automatic integrated 2-stage filtration
 - Increases oil longevity and quality
- Manual controls
 - Simple and ease to use
- Eco setting and fat melt mode
 - Reduces power consumption during pre-heating
- IPX5 rated
 - Easy and problem-free cleaning
- Supplied with fish grid, lid and oil bucket
 - Everything you need to operate the fryer
- Stainless steel panels with Scotch Brite finish
 - Looks great, ideal for front-of-house kitchens
- Dynamic Link System compatible
 - Integrated linking system allows quick and easy installation to create a seamless, continuous cookline

Accessories

- Front hob rail
- Kick strip
- Rear blanking plate
- Side hob extension
- Factory fitted, adjustable castors



Similar Models

- G9341F single pan gas fryer with filtration
- E9341 single pan electric fryer
- E3840F single pan electric fryer with filtration

F900

E9341F

Single Pan Electric Fryer with Filtration

Measurements *in mm*

Unit on castors is the same hob height

Specification *details*

Electrical rating (kW)	19	
Electrical supply voltage	400V 3N~ 50/60 Hz	
Required electrical supply (A)	32	
Electrical current split (A)	L1: 24.75, L2: 28.88, L3: 27.5	
Element rating (kW)	19	
Oil capacity (litres)	20	
Chip Output (kg/hr)	51	
Weight (kg)	70	
Packed weight (kg)	79	
Packed dimensions (w x d x h - mm)	490 x 1000 x 1015	
GTIN number	On feet	On castors

Short Form *specification*

Unit to be Falcon F900 Series high performance electric single pan fryer with in-built filtration. Pan will be 304 grade stainless steel. Unit to be supplied upon adjustable feet with a working oil capacity of 20 litres.

The pan will be of open well design to allow easy cleaning of the pan. Basket to be positioned at pan rear for oil drain off and storage.

Oil to be drained from pan into oil bucket that is to be self-contained inside the unit base. The oil temperature will be thermostatically controlled via precise controls from 130-190°C. The unit will have safety thermostat fitted as standard to prevent unit from overheating.

The hob will be constructed from 2mm 304 grade stainless steel. Hobs will be laser cut with right-angled edges to allow joining of units with no gaps between hobs. Exterior panels are Scotch Brite finish stainless steel. Control knobs to be marked showing temperature positions and to have a bezel behind each knob to prevent water ingress.

Installation note

Please consult local legislation with regard to installation of cooking equipment.



Falcon Foodservice Equipment, Wallace View, Hillfoots Road, Stirling FK9 5PY Scotland
t: +44 (0) 1786 455 200 e: info@falconfoodservice.com www.falconfoodservice.com

E9341F/SS/1120