



*Opus* **800**

#### PRODUCT OPTIONS AND ACCESSORIES

- OF2 Oil filter kit - size 2
- LK02 OPUS 350 LEG KIT
- OA8954 SPLASHGUARD FOR OPUS 800 ELECTRIC FRYERS

#### PRODUCT FEATURES

- Accurate thermostatic control up to 190°C for consistent results and safe operation
- Base model with oil drainage through the body of the fryer

Fry delicious food accurately with this Opus 800 Single-Tank Free Standing Single Tank Electric Fryer which comes with an accurate thermostatic control for consistent results and safe operation. The fryer is ideal for a variety of busy commercial kitchens, whether it's a large pub or a restaurant. The oil drains efficiently through the body of the fryer, while the hinged, lift out element with safety interlock makes it easy to access and clean the tank.

AIA FILE NUMBER:

ITEM NUMBER:



# LINCAT OPUS ELECTRIC FREE-STANDING SINGLE TANK FRYER - 2 BASKETS - W 400 MM - 14.0 KW

## MODEL: OE8114

### WEIGHTS & DIMENSIONS

|        |          |
|--------|----------|
| Width  | 400 mil  |
| Depth  | 800 mil  |
| Height | 1020 mil |
| Weight | 72.2 kg  |

### SHIPPING DETAILS

|                          |                         |
|--------------------------|-------------------------|
| Ship Width               | 85 cm                   |
| Ship Depth               | 45 cm                   |
| Ship Height              | 122 cm                  |
| Ship Weight              | 79.42 kg                |
| Ship Method              | LTL Common Carrier      |
| Shipping Package Type    | Pieces                  |
| Shipping Origin Zip Code | LN6 3QZ, UNITED KINGDOM |
| Quick Ship Product       | No                      |

### PRODUCT CERTIFICATIONS



### ENERGY SPECS

|                               |                              |                                      |                  |
|-------------------------------|------------------------------|--------------------------------------|------------------|
| Primary Energy Type           | Electric                     | Electrical Phase                     | 3-Phase          |
| Electrical Amps Per Conductor | L1=20.3; L2=20.3;<br>L3=20.3 | Electrical Plug Type                 | Hardwired        |
| Electrical Total Amperage     | 60.9 A                       | Number of Electrical Plugs           | Not Applicable   |
| Electrical Volts              | 400V                         | Electrical Connection Type           | Direct Hardwired |
| Electrical Total Wattage      | 14000 W                      | Number of Electrical Conductor Wires | 1                |
| Electrical Kilowatts          | 14 kW                        | Dedicated Circuit Required           | Yes              |
|                               |                              | Electrical Remarks                   | Three            |

### ADDITIONAL SPECIFICATIONS

|                        |   |                             |            |
|------------------------|---|-----------------------------|------------|
| Auto Oil Top-Off       | No  | Number of Baskets           | 2          |
| Basket Lift Type       | Not Applicable  | Number of Vats (batteries)  | 1          |
| Construction Materials | Stainless Steel   | Total Oil Capacity (volume) | 19 l       |
| Control Type           | Mechanical  | Oil Reclamation             | No         |
| Food Production Rate   | 40kg chips - 12mm<br>[frozen], 46kg chips -<br>12mm [chilled] per<br>hour | Oil Temperature Control     | Mechanical |
| Fryer Type             | Open Pot  | Pumped Oil Filtration       | No         |
| Integrated Filtration  | No  | Vat 1 Oil Capacity (volume) | 19 l       |
|                        |   | Ventless Cooking Technology | No         |
|                        |   | Split Pot                   | No         |
|                        |   | Temperature Maximum         | 190 °C     |

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated  
March 24, 2025

**BIDDING SPECIFICATIONS (SHORT FORM SPECS)**

Bidding Specifications Not Available.

**TECHNICAL DRAWING**

