



Product Code: EP1440H

Standard double door refrigerator cabinet



The EcoPro G3 range of cabinets offers a combination of cutting-edge refrigeration technology, low running costs and reliability, making them the first choice for the foodservice professional.

Features & Benefits


- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer - all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Market leading usable capacity, now supplied with 8 shelves as standard making your money go further – holds more than a conventional fridge
- Operates efficiently in ambient temperatures of up to 43°C

Shelving		Base Fittings		Doors	
Extra heavy duty shelving	Option	Castors 80mm	Standard	Left and right hinged door	Standard
8 shelves (GN2/1)	Standard	Legs 150mm	Option	Solid	Standard
Refrigeration		Electrical & Service Data		Product Extras	
R290 - Energy Efficient	Standard	230/50/1	Standard	Helicoil Mains Lead	Option
Integral Refrigeration System	Standard	Finish		Energy	
Less Condensing Unit	Option				
Specification		s/steel ext, 304 s/s door & alu int	Standard		
Gross volume (ltrs)	1350	304 s/s ext & int	Option	AEC	748
Refrigerator +1/+4°C	Standard	304 S/S back for island sitting	Option	Nett Volume	959.8
Width (mm)	1440			Energy Grade	B
Depth (mm)	855			Energy Efficiency Index	34.23
Height (mm)	2080				

Footnotes

- Castors not available if product supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 100mm
- Depth with door open is 1500mm

Energy Performance Data and information



Application


This appliance is intended for use in ambient temperatures up to 40°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



The Refrigeration Experts

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.